

# 6 User Pico 4 Ultra Enterprise Kit Specifications:

## DEVICES Pico 4 Ultra Enterprise

**Operating system**  
Pico OS

**System architecture/processor**  
Qualcomm Snapdragon XR2 Gen 2

**Memory (RAM)**  
12 GB

**Storage (ROM)**  
256 GB Internal

**Weight**  
580g with headstrap

**Display**  
Resolution: 2160x 2160 (x2)  
1200PPI (Pixels Per Inch)  
90Hz Refresh Rate

**Battery Life**  
Approx 3-4 hours

**Connectivity**  
USB Type-C  
WiFi Streaming

**Bluetooth® technology**  
Yes

**Wi-Fi**  
WiFi 7

**Speakers/microphones**  
Integrated stereo speakers  
Mic

**Sensors**  
Hand tracking



## Product Dimensions

Product Dimensions w795mm x d515mm x h350mm  
Weight 26kg

## INCHARGE CART

VR cases and Parotec specifications of electrics. Parotec Approvals:  
CE Approved  
ISO 9001 registered (2008)  
Solutions based around our 16 & 36 x Port PCB Intelligence Board have been subject to testing at Cass Industries Limited an compliance testing and CE marking partner for UK & EU requirements.

Parotec PCB Boards:  
PCB Inner board Power consumption:  
5V @ 34A maximum supply (each port is current limited to 2.1A)  
Robust design with up to 35 possible fixing holes on uniform 25mm centres  
IEC/EN 60335 compliant and CE certified  
Input voltage required up to 5.3V

Charge & Sync version of PCB also UL (USA) approved  
\*Charge Only boards currently used for VR kits. IF sending to US we would add Charge & Sync PCB's.

Parotec: Explorer Cases. Used to house all VR Kit.

Where no modification to the physical case is made these are fully waterproof and dust free.

Where we may have added external cooling fans the cases are reduced to weather proof and dust free.